

MATERIAL SAFETY DATA SHEET

MSDS

Last changed: 05/10/2000

Internal no.: 11

Replaces date:

JOTAFLOOR SOLVENT FREE PRIMER - COMP. A

1. PRODUCT AND COMPANY

- Approved for use
 Approved for laboratory use
 Approved by Jotun AS

TRADE NAME JOTAFLOOR SOLVENT FREE PRIMER - COMP. A

APPLICATION Two-pack. epoxyprimer

ART-NO PM3406

Producer/Importer JOTUN-HENRY CLARK LTD.

Address Flixborough, Scunthorpe

Zipcode & City North Lincolnshire DN15 8RR

Telephone +44 1724 40 00 00

Fax +44 1724 40 01 00

Contactperson QA/Environm. dept., JOTUN A/S, NORWAY

Responsible QA/Environm. dept., JOTUN A/S, NORWAY

Emergency number Contact the National Poison Center

2. COMPOSITION OF PRODUCT


No	Ingredients name	CAS-NO	Cons.(weight%)	Classification
1	EPOXY RESIN, LOW MOL. (MW<700)	25068-38-6	50-100	XiN;sens.,36/38-43-51/53
2	2,3-EPOXYPROPYL NEODECANOATE	26761-45-5	10-25	XiN;sens,43-51/53
3	BENZYLALCOHOL	100-51-6	2,5-10	Xn,20/22

Legend T+=Very toxic, T=Toxic, C=Corrosive, Xn=Harmful, Xi=Irritant, IK=No classification required, E=Explosive, O=Oxidising, F+=Extremely flammable, F=Very flammable, Fo=Flammable, N=Dang. to the environment, Mut=Genotoxic, Sens=Sensitizing, Carc=Carcero-gen, Repr=Causes birth defects

INGREDIENT COMMENTS

Substances presenting a health hazard within the meaning of the current issue of the CHIP Regulations or assigned occupational exposure limits.

3. HAZARD IDENTIFICATION



IRRITATING TO EYES AND SKIN. MAY CAUSE SENSITIZATION BY SKIN CONTACT.

For potential danger for the environment, see section 12.

4. FIRST AID

GENERAL

MATERIAL SAFETY DATA SHEET

MSDS

Last changed: 05/10/2000

Internal no.: 11

Replaces date:

JOTAFLOOR SOLVENT FREE PRIMER - COMP. A

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

INHALATION

Keep the patient warm in a quiet place with fresh air. If breathing has stopped, administer artificial respiration. If unconscious place in the recovery position. Seek medical advice.

SKIN CONTACT

Remove contaminated clothing. Wash skin thoroughly with soap and water or use an appropriate skin cleaner. Do NOT use solvents or thinners.

EYE CONTACT

Remove any contact lenses. Hold the eyelids apart. Irrigate copiously with clean, fresh water for at least 10 minutes. Seek medical advice.

INGESTION

DO NOT INDUCE VOMITING. If accidentally swallowed obtain immediate medical attention. Keep at rest. Seek medical advice.

MEDICAL INFORMATION

Regularly medical control. Person developing a skin rash are to be directed to a dermatologist for examination.

5. FIRE FIGHTING MEASURES

PROPER FIREFIGHTING EQUIPMENT

Recommended: alcohol resistant foam, CO₂, powders, water spray. Not to be used: water jet.

FIRE AND EXPLOSION HAZARDS

Fire will produce dense black smoke containing hazardous products of combustion (see Section 10). Decomposition products may be a hazard to health.

PERSONAL PROTECTION WHEN FIREFIGHTING

The personal protective equipment required is provided in section 8. Professional fire-fighters are required to use an air-fed system when dealing with major fires.

OTHER INFORMATION

Cool closed containers exposed to fire with water. Do not allow run-off from fire fighting to enter drains or water courses.

6. ACCIDENTAL RELEASE MEASURES

OTHER INFORMATION

Avoid breathing vapours. Refer to protective measures listed in sections 7 and 8. Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite and diatomaceous earth. Place in container for disposal according to local regulations (see section 13). Do not allow to enter drains or watercourses. Clean preferably with a detergent; avoid use of solvents. If the product enters drains or sewers, the local water company should be contacted immediately; in the case of contamination of streams, rivers or lakes, the Environmental Agency.

7. HANDLING AND STORAGE

HANDLING ADVICE

Avoid any skin contact with products containing epoxy; they may cause allergic reactions. Avoid skin and eye contact. Avoid inhalation of vapour and spray mist. For personal protective equipment see Section 8. Never use pressure to empty the container, it is not a pressure vessel. Always keep in containers made of the same material as the supply container. The Manual Handling Operations Regulations may apply to the handling of containers of this product.

STORAGE

Keep out of frost. Store in a dry, cold and well ventilated place away from sources of heat, ignition and direct sunlight. Observe the label precautions. Keep away from oxidizing materials, strongly alkaline materials and strong acids. No smoking. Containers which are opened should be properly resealed and kept upright to prevent leakage.

MATERIAL SAFETY DATA SHEET

MSDS

Last changed: 05/10/2000

Internal no.: 11

Replaces date:

JOTAFLOOR SOLVENT FREE PRIMER - COMP. A

8. EXPOSURE CONTROL AND PERSONAL PROTECTION

EXPOSURE CONTROL

Persons with allergic reactions to epoxy should not work with epoxy containing products. Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. OELs are taken from the current version of EH40 (by Health & Safety Executive, UK). Spray mist contains all substances of the product and must not be inhaled.

RESP. PROTECTION

When workers are facing concentrations above the occupational exposure limit they must use appropriate certified respirators. Use respiratory protective mask with charcoal and dust filter (A2/P2) when spraying this product.

EYE PROTECTION

Eye protection designed to protect against liquid splashes should be worn.

HAND PROTECTION

Use PVA/EVAL gloves. Barrier creams may help to protect exposed areas of the skin but are not substitutes for full physical protection. Never apply barrier cream to contaminated skin.

SKIN PROTECTION

Cotton or cotton/synthetic overalls or coveralls are normally suitable. Grossly contaminated clothing should be removed and the skin washed with soap and water or a proprietary skin cleaner. When spraying use suit covering the whole body.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form	Liquid.		
Colour	Light yellow.		
Odour	Faint.		
Solubility	Slightly soluble in: Water.		
Melting point/range	-	Density	1.12
Expl. limit LEL-UEL, %--%:	1,3-13,0	Solubility in water	
Vapor pressure		Saturation conc.	
Decomposition temp.		Rel. density sat. air (air=1)	
pH Solution		Boiling point/range	205°C
Flash point	100°C	pH concentrate	-
Molecular weight		Viscosity	
Ignition temp	435°C	Smelling limits lo-hi	
Rel. vapor density (air=1)		Rel. evap. velocity	
Air reactive		Water reactive	

10. STABILITY AND REACTIVITY

STABILITY

Stable under recommended storage and handling conditions (see section 7).

MATERIALS TO AVOID

Keep away from oxidising agents, strongly alkaline and strongly acidic materials to prevent the exothermic reactions.

HAZARDOUS DECOMPOSITION PRODUCTS

In a fire, hazardous decomposition products such as smoke, carbon monoxide, carbon dioxide and oxides of nitrogen may be produced.

MATERIAL SAFETY DATA SHEET

MSDS

Last changed: 05/10/2000

Internal no.: 11

Replaces date:

JOTAFLOOR SOLVENT FREE PRIMER - COMP. A

11. TOXICOLOGICAL INFORMATION

GENERAL

Based on the properties of the epoxyconstituents and considering toxicological data on similar preparations, this preparation may be a skin sensitizer and an irritant. It contains low molecular epoxy constituents which are irritating to eyes, mucous membrane and skin. Repeated skin contact may lead to irritation and to sensitisation, possibly with cross-sensitisation to other epoxies. Skin contact with the preparation and exposure to spray mist and vapour should be avoided.

INHALATION

Exposure to vapours may result in adverse health effects such as irritation of the mucous membrane and the respiratory system.

SKIN CONTACT

Products containing epoxy and amines may cause skin diseases e.g. allergic dermatitis. Repeated skin contact may lead to irritation and sensitization, possible with cross-sensitisation to other epoxies. Allergic reactions may occur after short time exposure.

EYE CONTACT

Splashes in the eyes may cause irritation and reversible local damage.

INGESTION

Accidental ingestion may cause vomiting and abdominal pains.

12. ECOLOGICAL INFORMATION

MOBILITY

2,3-Epoxypropyl neodecanoate: Flows on water. Absorbs to soil and will not be moveable.

BREAKDOWN

Epoxy resin, low mol. (MW<700): 12% (OECD 301B (mod.Sturm))

2,3-Epoxypropyl neodecanoate: Readily biodegradable.

ACCUMULATION

2,3-Epoxypropyl neodecanoate: Has the potential to bioaccumulate.

ECOTOXITY

Epoxy resin, low mol. (MW<700):

LC50 (Rainbow trout) = 1,5 mg/l (OECD 203)

EC50 (Daphnia) = 3,6 mg/l (OECD 202)

IC50 (Resp. inhibition activated mud) > 100 mg/l (EEC(1998))2,3-Epoxypropyl neodecanoate:

LC50 (Fish) = 1-10 mg/l. (Daphnia) = 10-100 mg/l.

EC50 (Algea) = 10-100 mg/l. (Bacteria) = >100 mg/l.

OTHER INFORMATION

The product should not be allowed to enter drains or water courses or be deposited where it can affect ground or surface waters. The product contains epoxy compounds labelled "Dangerous for the environment". The product contains 2,3-Epoxypropyl neodecanoate labeled "Dangerous for the environment".

13. DISPOSAL

Wastes, including emptied containers, are controlled wastes and should be disposed of in accordance with regulations made under the Control of Pollution Act and the Environmental Protection Act.

WASTEGROUP

08 00 00 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVE, SEALANTS AND PRINTING INKS. 08 01 02 Waste paints and varnish free of halogenated solvents.

MATERIAL SAFETY DATA SHEET

MSDS

Last changed: 05/10/2000

Internal no.: 11

Replaces date:

JOTAFLOOR SOLVENT FREE PRIMER - COMP. A

14. TRANSPORT INFORMATION



PROPER SHIPPING NAME	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID N.O.S. (Epoxy resin, low mol. MW <700,)		
Toll. reg. no.			
HAZCHEM			
ADR (Road)			
UN No.	3082	Dang. goods	
Class	9,11(c)	Label	9
Haz. id. no	90	Marginno.	
RID (Railway)			
UN No.	3082	Dang. goods	
Class	9,11 (c)	Label	9
Haz.id.no	90		
IMDG (Sea)			
UN No.	3082	Dang. goods	
Class	9	Label	9
Packaging group	III	EmS	-
MFAG	-	Marine Pollutant	
Sub. risk		Page	9028
IATA (Airplane)			
UN No.	3082	Dang. goods	
Class	9	Sub. risk	
Label	9	Packaging group	III


GENERAL

Transport only in accordance with ADR for road, RID for rail, IMDG for sea transport and IATA for airtransport.

15. REGULATORY INFORMATION



Classification



COMPOSITION

EPOXY RESIN, LOW MOL. (MW<700) (50-100), 2,3-EPOXYPROPYL NEODECANOATE (10-25)

R-PHRASES

R36/38 - Irritating to eyes and skin. R43 May cause sensitization by skin contact.

S-PHRASES

S23 Do not breathe vapour/spray. S24 Avoid contact with skin. S37-Wear suitable gloves. S38 In case of insufficient ventilation, wear suitable respiratory equipment. P92 Contains epoxy constituents - See information supplied by the manufacturer This information is supplied in the present MSDS.

REFERENCES

The product is labelled for supply in accordance with the current issue of CHIP Regulations, and latest version of the approved supply list.

16. OTHER INFORMATION



MATERIAL SAFETY DATA SHEET

MSDS

Last changed: 05/10/2000

Internal no.: 11

Replaces date:

JOTAFLOOR SOLVENT FREE PRIMER - COMP. A

PRINTED 05/10/2000

OUT:

VENDOR NOTES

Persons with epoxy allergic reactions, should not work with this kind of products. The Environmental Protection (Duty of Care) Regulations 1992 (SI 1992:2839). Further information and relevant advice can be found in: The Control of Substances Hazardous to Health Regulations 1988 (SI1988:1657). The Highly Flammable Liquids and liquefied Petroleum Gases Regulations 197 (SI 1972:917). The Manual Handling Operations Regulations 1992 (SI 1992:2793). Storage of Flammable Liquids in Containers, HS(G)51. Storage of Packaged Dangerous Substances, HS(G)71. The information contained in this MSDS is based on the present state of knowledge and current national legislation. As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with. The information in this MSDS provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications. The selection, use and maintenance of respiratory protective equipment: A practical guide HS(G)53.