

AQUAFILL

Water based Wall Filler



An Industrial Care
Company

Tel: 021-32201072 Email: Patsa.industrial@gmail.com

Web: www.patsaonline.com

Technical Data Sheet

PRODUCT DESCRIPTION

A ready mixed interior filler with easy sanding properties for the filling of cracks, holes and the smoothing of uneven surfaces.

USES

Suitable for interior use only as a thin coat putty for the finishing of rough surfaces and as filler for small cracks, holes and surface imperfections. Also suitable for repair work to interior plaster, fair – faced and lightweight concrete.

PROPERTIES

Appearance: Flat

Volume Solids: 73% ± 2%

Colour: White

Pack Size: 5 liters metal cans.

Spreading Rate: 3.2 sq. mtr. / kg / at 100 DFT
Depending on end use application method and thickness applied.

Drying Time: Surface dry in 1 hour. Re-coatable with itself after 2 hours and paintable after 10 hours. (in normal drying conditions).

Shelf Life: 12 Months when stored in dry and cool conditions.

APPLICATION DATA

Mix well before use. Apply by trowel, filling knife or spray. Apply sufficient AQUAFILL to fill or smooth surface.

Thinning: Do not thin, supplied ready for use.

Cleaning: Clean all tools and equipment immediately after use with clean water.

SPECIFICATION

Preparation

(New and Previously Decorated Surfaces)

All Interior Surfaces

All surfaces should be sound, clean, dry and free from loose and flaking material, dirt, efflorescence, oil, and curing compounds, from release agents, laitance and organic growth. See Notes [i, ii]

Unstable surfaces (powdery or chalky) should receive a coat of the appropriate PATSA AQUAPRIME before filling.

NOTES

- i. Organic growth (moss, fungus, mildew) should be treated with GloFlo QUAT in accordance with manufacturer's instructions.
- ii. New cement, plaster and concrete must have had ample opportunity to dry before filling (average 15 days)
- iii. On very dry absorbent surfaces wet the surface with sweet water prior to using the filler.

SAFETY INFORMATION

Use only in well ventilated areas.

Do not breathe vapor / spray.

In case of contact with eyes, rinse immediately with plenty of sweet water and seek medical advice.



PATSA Industrial Products & Services

Head office:

Steel House West Wharf Road,
Karachi-74000, (Pakistan)

Tel: 32201072

Fax: 92-21-32310976

Email: patsa.industrial@gmail.com

Distribution Office:

70/5 Timber Pond, Kemari,
East Wharf Road, Karachi-
75620

Ph: 32856602-32856601

Fax: 32856598