

AQUAMATT

Interior / Exterior Finish



An Industrial Care
Company

Tel: 021-32201072 Email: Patsa.industrial@gmail.com

Web: www.patsaonline.com

Technical Data Sheet

PRODUCT DESCRIPTION

An attractive matt finish, based on a blend of modern acrylic copolymers emulsion that provides a durable, washable surface with good color retention properties and resistance to yellowing and fading.

APPLICATION

An easy to apply finish coat for interior and exterior surfaces including cement, plaster, concrete, brick, stucco, building boards and gypsum boards.

PROPERTIES

Appearance: Matt

Color Range: Brilliant White

PATSA Color Range "Freedom to unlimited colors"

Volume Solids: 62% ± 2%

Pack Size: 5 liter and 16 liter

Spreading Rate: Up to 13 sq. mtr/ ltr.

(Depending on surface texture, porosity and application method)

Drying Time: Surface dry in 1 hour Recoatable after 3 hours (in normal drying conditions)

Shelf Life: 2 years when stored in dry and cool conditions

APPLICATION DATA

Stir well before use. Apply by brush, roller, air spray or airless spray. For details of spray equipment contact PATSA Technical Services Department: (021)32201072

Thinning

Brush and Roller: 0 – 5% sweet water (The first coat may be thinned up to 10% on very absorbent surfaces).

Airless Spray: 0 – 10% sweet water.

Cleaning

Clean all tools and equipment immediately after use with clean water.

Caution

Do not use when humidity levels may cause surface condensation (maximum 85%), during rainy conditions or if temperatures are likely to fall below 5°C during application and drying. Protect from frost.

SPECIFICATION

Preparation

(New and Previously Decorated Surfaces)

General

All surfaces should be sound, clean, dry and free from loose and flaking material, dirt, efflorescence oil, grease, wax and polish. Where appropriate the relevant PATSA primer should be used. Fill small cracks and surface imperfections with PATSA AQUAFILL, larger cracks may be filled with Asocret RN. See notes [i, ii]

Exterior Concrete, Brick, Render, Plaster, Gypsum board, Fiber board, etc.

Prime with one coat of PATSA AQUAPRIME and allow drying. See notes [i, ii, iv]



Decoration

(New and Previously Decorated Surfaces)

All Surfaces

Apply two coats of AQUAMATT Emulsion.

See notes [v, vi, vii, viii]

NOTES

- i.** Organic growth (moss, fungus, mildew.) should be treated with proprietary fungicidal treatments in accordance with manufacturer's instructions.
- ii.** On previously decorated surfaces, after the removal of loose and flaking material apply PATSA AQUAPRIME to bare areas overlapping onto the existing decoration.
- iii.** For the coating of non ferrous metals refer to PATSA technical service department.
- iv.** Surfaces of high porosity (very chalky and powdery) should be primed with one coat of ASO BA-FLEX diluted 1 : 1 with water.
- v.** For interior surfaces thin first coat to satisfy the porosity of the surface, a third coat may be required on very porous surfaces.
- vi.** A third coat may be required if there is a marked color contrast between the surface and the paint to be applied.
- vii.** On silk emulsion painted surfaces there is a possibility of cracking. Apply one coat of PATSA AQUAPRIME prior to finishing with PATSA AQUAMATT.

SAFETY INFORMATION

Use only in well ventilated areas. In case of insufficient ventilation during spraying, wear suitable respiratory equipment. Do not breathe vapor / spray. In case of contact with eyes, rinse immediately with plenty of sweet water and seek medical advice. Keep out of reach of children.

IMPORTANT NOTICE

These products are sold subject only to the expressed warranties contained herein. Additional warranties, expressed or implied, and any warranty of merchant ability is hereby excluded. Buyer agrees that seller assumes no liability for consequential damages of any kind, which result from the use or misuse of the merchandise sold hereunder. In the event that the buyer proves that any goods received do not conform to the specifications agreed to between the parties or if the buyer proves that such goods were defectively manufactured. The buyer's remedies shall be limited to either the return of the goods and repayment of the purchase price or replacement of the non-conforming goods at the option of the seller. Such remedy being exclusive of all others and the sole remedy available to the buyer, hereby expressly waives any claim to additional damages.



PATSA Industrial Products & Services

Head office:

Steel House West Wharf Road,

Karachi-74000, (Pakistan)

Tel: 32201072, 32313113

Fax: 92-21-32310976

Email: patsa.industrial@gmail.com

Distribution Office:

70/5 Timber Pond, Kemari,

East Wharf Road, Karachi-75620

Ph: 32856602-32856601

Fax: 32856598