Patsa Scratch Coat

Polymerized Cementitious Anchor Coat



Tel: 021-32201072 Email: Patsa.industrial@gmail.com Web: www.patsaonline.com

Technical Data Sheet

PRODUCT DESCRIPTION:

Patsa Scratch Coat is a specially designed polymerized cementitious coating that is applied as an roughening coat layer on floors and walls prior to application of consequent high build coating system. The application of the scratch coat helps the subsequent coat to adhere to the roughened tightly bonded coating by allowing the overcoat to enter the texturized profile and create a bond between the two layers.

RECOMMENDED USES

A special blend of cement, polymer and aggregates providing a bonding film between old and new concrete, bitumen primers, and all other surfaces suitable for membranes, paints, and various protective coatings.

Typical substrate includes:

- Concrete
- Cement
- Metal
- Wood
- Bitumen
- Polyurethane insulation boards
- And the vast array of building materials derived from these products

PROPERTIES

Spreading Rate: 1 sq. meter / KG

Drying Time: 4 hours **Application:** Single coat

Packing

25 KG bags



APPLICATION DATA

SPECIFICATIONS

Preparation

Surface to receive application must be structurally sound, and free of all dirt, oil, grease, paint, sealers, curing compounds, form release agents, or any other material that can act as a bond breaker or bond inhibiting agent.

SAFETY

Use only in well ventilated areas. In case of insufficient ventilation during application wear suitable respiratory equipment. Do not breathe vapor / spray.

In case of contact with eyes rinse immediately with plenty of sweet water and seek medical advice. Keep out of reach of children.

IMPORTANT NOTICE

These products are sold subject only to the expressed warranties contained herein. Additional warranties, expressed or implied, and any warranty of merchant ability is hereby excluded. Buyer agrees that seller assumes no liability for consequential damages of any kind, which result from the use or misuse of the merchandise sold hereunder. In the event that the buyer proves that any goods received do not conform to the specifications agreed to between the parties or if the buyer proves that such goods were defectively manufactured. The buyer's remedies shall be limited to either the return of the goods and repayment of the purchase price or replacement of the non-conforming goods at the option of the seller. Such remedy being exclusive of all others and the sole remedy available to the buyer, hereby expressly waives any claim to additional damages.



PATSA Industrial Products & Services

Head office:

Steel House West Wharf Road, Karachi-74000, (Pakistan) Tel: 32201072, 32313113

Fax: 92-21-32310976 Email: patsa.industrial@gmail.com

Distribution Office:

70/5 Timber Pond, Kemari, East Wharf Road, Karachi-75620 Ph: 32856602-32856601

Fax: 32856598

Http: www.patsaonline.com