



## Technical Data Sheet

# BLANKOL-5006

## Release Agent

Art.-No. 4 06110

### Fields of Application:

BLANKOL-5006 has been particularly designed for the precast element production.

### Properties and Benefits:

BLANKOL-5006 is an environmentally friendly, high-quality release agent, which does not support build-ups and reduces the formation of superficial pores due to selected active components.

### Technical Data:

Colour:	clear, yellowish
Form:	liquid
Density:	0.8 g/cm <sup>3</sup>
Storage:	Not frost sensitive, in closed container, keep away from dirt.
Shelflife:	24 months in closed containers
Packaging:	1.000 l IBCs 180 l drums 25 l cans

### Consumption:

15 - 50 g/m<sup>2</sup>  
Depending on the type of mould.

### Instructions for Use:

BLANKOL-5006 is to be sprayed regularly and as thin as possible onto the clean and dry mould.

### Special Advice:

- Suitability tests should be carried out prior to usage.
- Avoid puddles!
- Excessive coating can lead to incrustations and build-ups.
- Only use spray nozzles with a maximum diameter of 1 mm.
- Do not drain off the treated surfaces, but wipe up surplus release agent with a mineral oil resistant squeegee.
- BLANKOL-5006 is not water soluble
- Welding, flying sparks, open fire etc. must be absolutely avoided next to freshly treated moulds.

### Safety Regulation:

Please adhere to the European Safety Data Sheet (MSDS)!