



REINIT-Natur

Art.-No. 4 06154

Machine care

Properties and Benefits:

REINIT-Natur prevents the adhesion of concrete and mortar residues, does not attack metal or lacquer. Reduces rust formation on the treated metal parts. Regular application of REINIT-Natur prolongs the service life of machinery and equipment. REINIT-Natur is fully biologically degradable.

Fields of Application:

REINIT-Natur is to be applied generally when adhesion of concrete or mortar should be prevented. It is especially suitable as an anti-corrosive for construction and tarmac machinery or truck mixers that are temporarily shut down (e.g. for 2 to 3 months). Sand-blasting or time-consuming and costly derusting is obsolete.

Technical Data:

Colour:	yellow
Form:	liquid
Density:	0,90 g/cm ³
Storage:	protect against frost, in closed container
Shelf-life:	12 months in closed original containers
Packaging:	1000 l IBCs 180 l drums 25 l cans
Consumption:	150 - 200 g/m ²

Instructions for Use:

New equipment has to be sprayed with REINIT-Natur before use. Used or soiled building equipment should be cleaned with a high pressure hose before first use. Larger concrete and mortar residues must be removed mechanically and be pretreated with REINIT-R if necessary. As soon as the metal surface is dry and clean, REINIT-Natur is to be applied until saturation (undiluted) by suitable painting or spraying equipment. Use nozzle jets of approx. 2 mm diameter!

Special Advice:

- Our recommendations are only guidelines.
- Suitability tests should be carried out prior to usage.

Safety Advice:

Please adhere to the European Safety Data Sheet (MSDS)!